

# Sassi Lift Systems Limited

## BF1D-1, 2D-1 & 2D-2 Safety Gear Enquiry / Order Form

General Specification : Please complete & return

Quantity required (pairs) = \_\_\_\_\_  
Rated load = \_\_\_\_\_ kg  
Rated speed = \_\_\_\_\_ m/sec  
Car weight = \_\_\_\_\_ kg  
Weight of compensating ropes = \_\_\_\_\_ kg (if applicable)  
Mass of counterweight = \_\_\_\_\_ kg  
Traction Sheave Diameter = \_\_\_\_\_ mm  
Roping = \_\_\_\_\_ : 1

Mounting  Car Sling (top)  Car sling (bottom)  
Guide Rail  9mm  16mm  
Type  Machined  Cold drawn  
Rail Surface  Dry  Lubricated  
 6.5 mm Accessory set  8mm Accessory set  
 Pull Rod – 625mm long (standard)  Pull Rod – 3500mm long (option)  
 Safety switch without locking (standard)  Safety switch with locking (option)

Sassi Lift Systems should reply to:

Company : \_\_\_\_\_ Date : \_\_\_\_\_  
Attn : \_\_\_\_\_ Ref : \_\_\_\_\_  
Phone : \_\_\_\_\_ Email : \_\_\_\_\_  
Fax : \_\_\_\_\_

Tel: 01376 550666

Fax: 01376 341219